



Evo Prime Led Light bar



Most Comprehensive Light Output

The Evo Prime provides the most bulk lighting for the best light spread. Featuring 10 Watt LEDs, Prime Drive Technology and an IP-68 rating, the Evo Prime is the right LED light for offroading to commercial applications.

Evo Prime Series Usage Guide

10 WATT LED BULK LIGHTING

Achieve the most comprehensive light output with the 10 watt next-gen LEDs in the Evo Prime Series.

PRIME DRIVE TECHNOLOGY

With Prime Drive, Electronic Thermal Management maintains a safe operating temperature for the light without sacrificing output.

DIMMING CAPABILITY

Pulse Width Modulation circuitry flashes the LED faster than the human eye can see to achieving dimming capability.

EXTRUDED ALUMINIUM

Extruded 6061 Aluminium is used to achieve an ingress Protection rating of IP-68, creating a light bar with unmatched durability and protection.

PART#	Beam Pattern	Raw Lumens	Dimensions	Weight	Wattage
XIL-EP220	20° Narrow	1,720 lm(ea)	117.4/54.4/92.1 mm	1.1 kg	20 Watt
XIL-EP240	40° Wide	1,720 lm(ea)	117.4/54.4/92.1 mm	1.1 kg	20 Watt
XIL-EP420	20° Narrow	3,440 lm(ea)	197/54.4/92.1 mm	1.6 kg	40 Watt
XIL-EP440	40° Wide	3,440 lm(ea)	197/54.4/92.1 mm	1.6 kg	40 Watt
XIL-EP620	20° Narrow	5,160 lm(ea)	276.6/54.4/92.1 mm	2.1 kg	60 Watt
XIL-EP640	40° Wide	5,160 lm(ea)	276.6/54.4/92.1 mm	2.1 kg	60 Watt
XIL-EP1020	20° Narrow	8,600 lm(ea)	435.8/54.4/92.1 mm	3.1 kg	100 Watt
XIL-EP1040	40° Wide	8,600 lm(ea)	435.8/54.4/92.1 mm	3.1 kg	100 Watt
XIL-EP1220	20° Narrow	10,320 lm(ea)	515.4/54.4/92.1 mm	3.6 kg	120 Watt
XIL-EP1240	40° Wide	10,320 lm(ea)	515.4/54.4/92.1 mm	3.6 kg	120 Watt
XIL-EP1820	20° Narrow	15,480 lm(ea)	754.2/54.4/92.1 mm	5.1 kg	180 Watt
XIL-EP1840	40° Wide	15,480 lm(ea)	754.2/54.4/92.1 mm	5.1 kg	180 Watt
XIL-EP2420	20° Narrow	20,640 lm(ea)	993/54.4/92.1 mm	6.6 kg	240 Watt
XIL-EP2440	40° Wide	20,640 lm(ea)	993/54.4/92.1 mm	6.6 kg	240 Watt
XIL-EP3220	20° Narrow	27,520 lm(ea)	1311.4/54.4/92.1 mm	8.6 kg	320 Watt
XIL-EP3240	40° Wide	27,520 lm(ea)	1311.4/54.4/92.1 mm	8.6 kg	320 Watt



Evo Prime Features

- ▶ Weatherproof Deutsch Connector with Plug and Play Harness
- ▶ Integrated Electronic Thermal Management
- ▶ Billet Clamp Tube Frame Mounts Available
- ▶ Next Gen LED is Driven to 90% Efficiency
- ▶ PWM Integrated Dimming Circuitry
- ▶ Extruded 6061 Aluminum Housing
- ▶ Advanced Heat Sink Design
- ▶ Polycarbonate Lens
- ▶ Patent # US 7,950,821 B1

Billet Tube Frame Mounts

360° Tube Frame Mount System TUBE MOUNTS

Machined Billet Clamps fit Evo Prime Series Light Bars for tubed frame or chassis mounting.



XIL-B175 (45mm) Shown Features

- ▶ Machined Billet 6061 Aluminum
- ▶ Includes All Mounting Hardware
- ▶ Laser Engraved Vision X Logo
- ▶ Sold in Pairs
- ▶ Diameter: 19mm - 25mm - 32mm - 38mm - 43mm - 45mm - 51mm

